

	external ø	no. of holes	centre to centre dist.	holes ø
TYPE 1 Flange	203	6	178	7,5
TYPE 2 Flange	203	3	178	7,5
TYPE 3 Flange	140	4	120	7
TYPE 4 Flange	140	4	118	13
TYPE 5 Flange	105	4	90	7
TYPE 6 Flange	180	4	160	8,5
TYPE 7 Flange	154	4	142	7
Flange DIN40	150	4	110	18



Range	Model	Flange TYPE 1	Flange TYPE 2	Flange TYPE 3	Flange TYPE 4	Flange TYPE 5	Flange TYPE 6	Flange TYPE 7	Flange DN40
PFG05	STANDARD	√							
	PFG05C	√							
	PFG05X	X							
	PFG05AT	X							
	PFG05ATFV		X						
	PFG05ATFV 400°		X						
	PFG05ATFV 600°		X						
PFG57	STANDARD			√		√			
	PFG57X			X					
	PFG57AT			X					
	PFG5742-42T			√					
PFG09	STANDARD			√		√			
	PFG09Z			√					
	PFG09ZATF			X					
PFG06	STANDARD			√					
MN03	STANDARD						X		
MN21	STANDARD						X		
	MN21...F							X	
PFGLP	STANDARD-C							X	
PFGLP22	PFGLP22F-FC				X				
SMD20	STANDARD	direct connection, with 4 holes ø6 with centre to centre distance 90 mm							
	SMD20F	version with special flange ø135, with 4 holes ø6,5 centre to centre distance 120 mm							
	SMD20ST	fixing bracket with 2 holes ø8,5 distance 70 mm							
	SMD20VN	fixing bracket with 2 holes ø8,5 distance 70 mm							
	SMD20P	fixing bracket with 2 holes ø8,5 distance 70 mm							

X = standard process connection of the model

√ = available option