



PLASTIC PADDLES



AC1

1 Nylon 6 blade.

50 x 100 mm

Minimum material density: **1,0 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2 - G 1" 1/4**

Min. hole ø
39 mm

Material/weight*



AC2

3 Nylon 6 blades.

120 x 70 mm

Minimum material density: **0,3 kg/dm³**

Installation with flange or from inside the silo

Min. hole ø
125 mm

Material/weight*



AC4

1 Nylon 6 blade.


52 x 100 mm

Minimum material density: **0,5 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
65 mm

Material/weight*



AC9

1 Nylon 6 blades.


140 x 65 mm

Minimum material density: **0,2 kg/dm³**

Installation with flange or from inside the silo

Min. hole ø
145 mm

Material/weight*



AC13

2 Nylon 6 blades.

304 x 142 mm

Minimum material density: **0,02 kg/dm³**

Installation with flange or from inside the silo

Min. hole ø
305 mm

Material/weight*



AC19

1 Lathiom 52/11-08 PD02 blade.

Suitable for use in contact with food products.

130 x 70 mm

Minimum material density: **0,3 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2 - G 1" 1/4**

Min. hole ø
39 mm

Material/weight*



***Very light:** e.g. polystyrene - **Light:** e.g. ash - **Medium:** e.g. corn, flour, coffee grains, wheat - **Heavy:** e.g. gravel



STAINLESS STEEL PADDLES



Min. hole ø
39 mm

Material/weight*



AC1-INOX

1 AISI 304 stainless steel blade.

50 x 100 mm

Minimum material density: **1,0 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2 - G 1" 1/4**



Min. hole ø
105 mm

Material/weight*



AC3-INOX

4 AISI 304 stainless steel blades.

100 x 50 mm

Minimum material density: **0,3 kg/dm³**

Installation with flange or from inside the silo



Min. hole ø
65 mm

Material/weight*



AC4-INOX

1 AISI 304 stainless steel blade.

57 x 100 mm

Minimum material density: **0,5 kg/dm³**

Suitable for: **G 2" 1/2**



Min. hole ø
140 mm

Material/weight*



AC5-INOX

4 AISI 304 stainless steel blades.

138 x 50 mm

Minimum material density: **0,2 kg/dm³**

Installation with flange or from inside the silo



Min. hole ø
100 mm

Material/weight*




AC5L-INOX

4 AISI 304 stainless steel blades.

100 x 100 mm

Minimum material density: **0,2 kg/dm³**

Installation with flange or from inside the silo



Min. hole ø
110 mm

Material/weight*



AC6-INOX

1 AISI 304 stainless steel blade.

138 x 145 mm

Minimum material density: **0,1 kg/dm³**

Installation with flange or from inside the silo

***Very light:** e.g. polystyrene - **Light:** e.g. ash - **Medium:** e.g. corn, flour, coffee grains, wheat - **Heavy:** e.g. gravel



STAINLESS STEEL PADDLES



AC7-INOX

1 AISI 304 stainless steel blade.

57 x 145 mm

Minimum material density: **0,3 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
65 mm

Material/weight*



AC8-INOX

4 AISI 304 stainless steel ropes.

Diameter: **260 mm**

Minimum material density: **2,0 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
100 mm

Material/weight*



AC9-INOX

2 AISI 304 stainless steel blades.

140 x 65 mm

Minimum material density: **0,2 kg/dm³**

Installation with flange or from inside the silo

Min. hole ø
145 mm

Material/weight*



AC10-INOX

2 AISI 304 stainless steel blades.

70 x 135 mm

Minimum material density: **0,6 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
75 mm

Material/weight*



AC11-INOX

4 AISI 304 stainless steel blades.

150 x 100 mm

Minimum material density: **0,1 kg/dm³**

Installation with flange or from inside the silo

Min. hole ø
155 mm

Material/weight*



AC12-INOX

1 AISI 304 stainless steel blade.

160 x 80 mm - Width: 30 mm

Minimum material density: **0,4 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2 - G 1" 1/4 - G 1"**

Min. hole ø
30 mm

Material/weight*



***Very light:** e.g. polystyrene - **Light:** e.g. ash - **Medium:** e.g. corn, flour, coffee grains, wheat - **Heavy:** e.g. gravel



STAINLESS STEEL PADDLES



AC14-INOX

1 AISI 304 stainless steel blade.


115 x 157 mm - Width: 28 mm

Minimum material density: **0,4 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2 - G 1" 1/4 - G 1"**

Min. hole ø
30 mm

Material/weight*



AC15-INOX

1 AISI 304 stainless steel blade.

127 x 157 mm - Width: 68 mm

Minimum material density: **0,2 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
70 mm

Material/weight*



AC16-INOX

1 AISI 304 stainless steel blade.

110 x 152 mm - Width: 40 mm

Minimum material density: **0,3 kg/dm³**

Suitable for: **G 2" 1/2 - G 1" 1/2**

Min. hole ø
42 mm

Material/weight*



AC17-INOX

4 AISI 304 stainless steel blades.

74 x 100 mm

Minimum material density: **0,4 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
72 mm

Material/weight*



AC18-INOX

4 AISI 304 stainless steel blades.

70 x 50 mm

Minimum material density: **0,7 kg/dm³**

Suitable for: **G 2" 1/2**

Min. hole ø
72 mm

Material/weight*



***Very light:** e.g. polystyrene - **Light:** e.g. ash - **Medium:** e.g. corn, flour, coffee grains, wheat - **Heavy:** e.g. gravel